

Technical Data Regional Coach Car Bnrdzf 463, 470, 476, 477



| Entrance from platforms | 350mm 760mm |
|--------------------------------------|--|
| Entrance height | 550mm |
| Doors per side | 2 doors with 2 leaves each |
| Type of doors | slam doors (revolving folding doors) |
| Number of standard seats | 64 |
| Number of flip-up seats | 14 18 |
| Layout of sitting area | two areas with central corridor and bay-seating in 2+2 arrangement |
| Layout of multi-purpose area | 14 18 flip-up seats in large multi-purpose area |
| Driver-cab | for reversible train |
| Remote control for locomotive | conventional 36 pole line – partly ZWS |
| Traction types for locomotive | Diesel or electric |
| Windows | fixed and sliding |
| Interchangeability | German homologation |
| Top speed in passenger operation | 140km/h |
| Bogie type | Minden-Deutz 43 (MD43) |
| Total weight | 29t 36t |
| Length over buffers | 26 400mm |
| Length of car-body | 25 805mm |
| Width of car-body | 2 825mm |
| Height of car-body above top of rail | 4 050mm |
| Distance between bogie centres | 19 000mm |
| Wheel-base (bogie) | 2 500mm |
| Diameter of new wheels | 950mm |
| Diameter of worn wheels | 900mm |
| Brake type | pneumatic self-adjusting load-proportional disc brake |
| | (R KE-GPR-A (D)) |
| Number of brake-cylinders per bogie | 2 |
| Energy supply | train line and static battery chargers |
| Battery | 24V |
| Lighting | fluorescent lamps |